

## ATTACHMENT B

### SUBSTITUTE SPECIFICATION

(Showing All Changes Made to the Published Specification in International Application  
No. PCT/SE2005/000127)

### A BEVERAGE PACKAGING UNIT

#### BACKGROUND OF THE INVENTION

##### FIELD OF THE INVENTION

The present invention relates to a beverage packaging unit.

##### DESCRIPTION OF THE RELATED ART

In present ~~days~~ day society people drink a large number of different sorts of ~~beverage~~ beverages, for instance aerated or carbonated beverages, juices, milk, milk-based beverages, and also packaged beer, ale, and wine, for instance in portion-wise packaging units.

The most common packaging units for present day beverages are bottles of varying sizes each with its characteristic appearance, i.e., a cylindrical package ~~which~~ that narrows at its top to form an orifice from which the beverage can be drunk ; ~~wherewith the~~ . The orifice can be re-sealed with the aid of a screw-threaded cork or a screw cap. The bottles are normally made of plastic, such as PET, or glass.

Another type of common packaging unit is an ~~aluminium~~ aluminum can of cylindrical shape, so as to enable such cans to be mutually stacked, and ~~comprising~~ including a characteristic can opening procedure in which part of the ~~aluminium~~ aluminum end in the form of a tab is broken away from the upper side end of the can ~~and therewith create a hole~~ to provide an opening from which the contents of the package can be drunk.

Another common type of packaging unit is ~~the a~~ Tetra Pak Pak<sup>®</sup> unit with which a plastic wrapped drinking straw is glued to one of the two largest side surfaces of the Tetra Pak Pak<sup>®</sup> unit. The contents of ~~this~~ that packaging unit are typically drunk by removing the straw from the unit and then removing the plastic wrapping and inserting the straw down through a hole provided in the upper side of the Tetra Pak Pak<sup>®</sup> packaging unit and that is covered with ~~aluminium~~ aluminum foil. The contents of the Tetra Pak Pak<sup>®</sup> unit can then be drunk through the straw.

Another common beverage packaging unit is a glass bottle that includes a cap fitted over the neck orifice of the bottle, and ~~a hole~~ an opening from which the bottle contents can be drunk.

All types of packaging units have certain positive and negative aspects. Generally speaking, some packaging units are not transport effective because they cannot be packed tightly together, while others cannot be re-sealed, and because some other packaging units are unhygienic. The drawbacks are described in more detail hereinafter.

One problem with respect to some packaging units is that they are transported over long distances, most often in large freight vehicles. The shape of cylindrical beverage packaging units prevents optimal use of the freight volume of the vehicle. The typical PET bottles are usually placed in crates, which are then stacked firmly one upon the other. ~~This~~ That means that large volumes around the bottles and above and beneath respective bottles goes go unused. ~~This~~ That problem thus also exists with all cylindrical packaging units that have a tapering upper part, where either a screw cork or a screw cap is affixed. Another packaging unit that constitutes a part of this

problem is the typical ~~aluminium~~ aluminum can. ~~This can~~, which is also cylindrical and ~~therewith~~ therefore also results in unused freight volume around the cans.

Another problem with many beverage packaging units is that they can not be re-sealed. When such a packaging unit has been opened on a given occasion [[.]] in order to drink its contents, it is normally either necessary for the person concerned to empty the unit of its contents at one and the same time or to throw away beverage that he/she does not wish to drink subsequent to having opened the unit.

The person drinking from ~~the~~ a packaging unit will normally wish to drink a small amount, often at different times, and be able to re-seal the unit so that its ~~content~~ remaining contents can be drunk later on. One solution to ~~this~~ that problem exists ~~in the~~ is a bottle that is sealed with a screw-on cork, for instance ~~the~~ a PET-bottle, although ~~these~~ those bottles have less effective freight-volume properties, as mentioned above. Other typical beverage packaging units, such as ~~aluminium~~ aluminum cans, glass bottles provided with caps, or Tetra Pak Pak® packaging units, cannot be re-sealed.

The unhygienic packaging unit ~~present~~ presents a further problem. ~~Aluminium~~ Aluminum cans are exposed to the surroundings from the manufacture and then during transportation, e.g., to the grocery store, and then ~~in~~ within the store itself, and subsequently, until the liquid in respective cans has been drunk. In order to drink from the can, the can is opened and the part of the can that is folded away to provide an opening through which the ~~content~~ contents of the can be drunk is folded down into the can, i.e., down into the liquid that is later to be drunk. Some packaging units, among them ~~aluminium~~ aluminum cans, are designed so that the person drinking from

the unit is forced to place his/her mouth directly against a part of the packaging unit which, as earlier mentioned, has been exposed to the surroundings from the manufacture of the can until the person concerned drinks from the unit. Moreover, the liquid is drunk from the can ~~[[,]]~~ into which the can part that has been folded away to provide ~~said~~ the opening has been immersed. The person who drinks the liquid in the can is ~~therewith~~ thereby exposed ~~for instance~~ to bacteria, virus, and/or toxic substances, for instance, as a result of the direct contact of the person's mouth with both the can and the liquid, which is unhygienic.

One further drawback and problem encountered with the Tetra Pak Pak<sup>®</sup> packaging unit that includes a drinking straw is that the Tetra Pak Pak<sup>®</sup> unit is deformable, ~~meaning that~~ . Consequently, when the unit has been opened with the aid of the straw, and while gripping the Tetra Pak Pak<sup>®</sup> unit with unaccustomed fingers ~~[[,]]~~ the unit is squeezed together to such an extent that liquid will gush from the Tetra Pak Pak<sup>®</sup> unit like a fountain and therewith land outside the unit.

All of the ~~aforsaid~~ above-described problems associated with known beverage packaging technology are solved by means of the present invention, which provides a stackable and re-sealable and hygienic beverage packaging unit.

## SUMMARY OF THE INVENTION

Accordingly In accordance with the present invention there is provided in ~~accordance with the invention~~ a beverage packaging unit that includes an opening from which the liquid contents of the unit can be drunk or poured, ~~wherewith said~~ . The opening, or orifice, can be closed with the aid of ~~an~~ a closure element, ~~wherein~~

~~the invention is characterized in that the~~ . The packaging unit is ~~parallelepipedic~~ parallelepipedal in shape and includes a hollow, box-like body and ~~said the~~ closure element ; ~~in that said~~ . The ~~parallelepipedic~~ parallelepipedal, hollow, box-like body has a bevelled corner at which there is formed a three-sided, or triangular, surface that ~~connects~~ is connected with ~~said the~~ box-like body ; ~~in that there projects out~~ . Projecting outwardly from said the triangular surface is a tubular part that includes ~~said the~~ opening or orifice ; ~~in that said~~ . The closure element includes a generally pyramidal body ~~which that~~ is shaped so that when in abutment with ~~said the~~ bevelled corner of ~~said the~~ box-like body it forms, together with ~~said the~~ body, ~~said the~~ parallelepipedic parallelepipedal packaging unit ; ~~in that said~~ . The closure element includes a cavity for receiving ~~said the~~ tubular part ; ~~and in that the~~ . The packaging unit includes co-acting fasteners on ~~said the~~ tubular part and also in ~~said the~~ cavity for removably retaining ~~said the~~ closure element at ~~said the~~ tubular part, so that ~~said the~~ box-like body and ~~said the~~ closure element ~~will~~ form a parallelepiped.

#### BRIEF DESCRIPTION OF THE DRAWINGS

The invention will now be described in more detail, partly with reference to an exemplifying embodiment of the invention illustrated in the accompanying drawings, in which

- Figure 1A ~~illustrates~~ shows a side view of a packaging unit ~~according to in~~ accordance with the invention, in which ~~the an~~ outwardly projecting tubular part is placed on ~~the a~~ three-sided surface of ~~the a~~ box-like body ~~and constitutes the to~~ provide an opening from which liquid beverage ~~is able to run out~~ can be dispensed,

and also shows the opening closure part of the packaging unit in abutment with the three-sided surface of the box-like body;

- ~~Figure 1B illustrates the packaging unit according to the invention in which the outwardly projecting tubular part is shown placed on the three sided surface of the box like body, said surface constituting the opening from which beverage is able to run out, wherein the figure shows~~ is an exploded side view of the packaging unit shown in Figure 1A with the closure part of the packaging unit released from the outwardly projecting tubular part of the box-like body;

- Figure 2A ~~shows~~ is a side view of the packaging unit ~~according to figure shown in Figures 1A-1B~~ including a pipe tube or drinking straw inserted in the outwardly projecting tubular part and showing the closure element in abutment with the three-sided surface of the box-like body;

- Figure 2B ~~illustrates the invention according to figures 1A-1B and shows a pipe or drinking straw in the outwardly projecting tubular part, wherewith~~ is an exploded side view of the packaging unit shown in Figure 2A with the closure element is shown loosened from the outwardly projecting tubular part of the box-like body but still in contact with the pipe or straw.

- Figure 2C ~~illustrates the inventive packaging unit according to figures 1A-1B and shows a pipe or drinking straw inserted in the outwardly projecting tubular part and also shows~~ is an exploded side view of the packaging unit shown in Figures 1A and 1B with the opening closure element fully released from the outwardly projecting tubular part and from the pipe or straw inserted in said the tubular part;

- Figure 2D is an enlarged, fragmentary side view of the opening closure element shown in ~~figure~~ Figure 2C, including the cavity, the straw, and the outwardly projecting tubular ~~party~~ part.

### DESCRIPTION OF THE PREFERRED EMBODIMENTS

Figures 1A ~~[[,]]~~ and 1B ~~of the present invention relate to~~ show a beverage packaging unit 1 in accordance with the present invention that ~~comprises~~ includes a ~~parallelepipedic~~ parallelepipedal, hollow, box-like body 2, and an opening closure element 3. An opening 8 is provided through which a beverage contained in the body 2 can be drunk ~~, said~~ . The opening 8 ~~being~~ is sealable with the aid of ~~said~~ closure element 3.

The packaging unit 1 is ~~parallelepipedic~~ parallelepipedal in shape and ~~comprises~~ includes the hollow box-like body 2 and the opening closure element 3. One of the corners of the ~~parallelepipedic~~ parallelepipedal hollow body 2 is bevelled to provide a three-sided ~~[[,]]~~ or triangular ~~[[,]]~~ surface 7. ~~This three-sided surface 7 connects that is connected~~ with the box-like body 2. An outwardly projecting tubular part 4, which includes ~~said~~ opening 8, is located on the ~~three-sided~~ triangular surface 7.

The opening closure ~~part~~ element 3 includes a generally pyramidal body that is so configured ~~so~~ that when the opening closure element 3 is in abutment with the ~~three-sided~~ triangular surface 7 at the bevelled corner of the box-like body 2, ~~said-the~~ pyramidal body will form ~~said-parallelepipedic~~ the parallelepipedal beverage packaging unit 1 together with the box-like body 2. The opening closure element 3 includes a

cavity 6 ~~which is intended to receive~~ for receiving the tubular part 4. Mutually co-acting fasteners fastening means 10, for instance snap fasteners or screw threads, are provided on both the tubular part 4 and in the cavity 6. ~~These~~ The co-acting fasteners ~~retain~~ fastening means releasably ~~said~~ retain the opening closure element 3 on the tubular part 4, so that the box-like body 2 and the opening closure element 3 will form ~~said parallelepipedic~~ the parallelepipedal packaging unit 1.

~~According to~~ In accordance with one embodiment of the invention there is included ~~said~~ tubular part 4 and ~~said~~ opening 8 through which beverage contained in the box-like body 2 ~~will run out~~ is dispensed.

Figures 2A-2D illustrate a further embodiment in which a ~~pipe~~ tube 5, such as a drinking straw, made of an appropriate plastic material, is firmly fixed ~~, said~~ relative to box-like body 2. ~~The~~ straw preferably ~~being~~ is an expandable or non-expandable straw that extends through the tubular part 4 down into the interior of the box-like body 2, with the bottom end 20 of the straw 5 in contact with the bottom 21 of the box-like body 2.

The ~~pipe~~ tube 5 inserted down into ~~said~~ tubular part 4 is expandable along a ~~part~~ portion extending from ~~said~~ tubular part 4. The ~~pipe~~ tube 5 ~~will~~ preferably ~~include~~ includes an outwardly-extending edge 16 ~~which is positioned so as to come into~~ abutment with the inside surface 17 of the body 2. ~~This will to~~ prevent displacement of the ~~pipe~~ tube 5 from its position ~~in~~ within the box-like body. The edge 16 is resiliently deformable to the extent that the edge 16 ~~will be deformed~~ deflect when the pipe is pressed down through the tubular part 4. Subsequent to the ~~pipe~~ tube 5 and the edge 16 having been forced down into the box-like body 2, the edge 16 will return



to its original form and ~~constitute~~ serve as an obstacle to withdrawal of the pipe tube 5 from the box-like body 2, or to outward movement of the pipe tube 5 away ~~up~~ from the bottom 21 of said box-like body 2.

~~According to~~ In accordance with one embodiment, the pipe tube 5 ~~lack~~ lacks the edge 16, ~~therewith~~ thereby enabling the pipe tube 5 to be freely withdrawn ~~freely~~ from the box-like body 2 and, likewise, enabling the tube 5 to be freely inserted into said the body.

In one embodiment of the invention, with the tubular part 4 ~~as said~~ including the opening, the ~~fastener~~ fastening means 10 is a snap-in fastener. ~~The~~ As shown in Figure 1B, the snap-in fastener preferably ~~comprises a~~ includes an outwardly-extending shoulder or lip 13 located externally on the tubular part 4, and a shoulder-~~hooking~~ receiving recess 14 located inside the cavity 6 ~~on~~ of the closure element 3. The ~~fastener~~ fastening means 10 is adapted so that the closure element 3 can be rotated ~~around~~ relative to the tubular part 4. The closure element 3 is removed from the tubular part 4, preferably by twisting said the element 3 so that the corners of said the element ~~will be~~ are free from the ~~three-sided~~ triangular surface 7. The closure element 3 is then ~~drawn over orthogonally in the free standing corners~~ withdrawn orthogonally from shoulder or lip 13 and ~~out~~ away from the ~~three-sided~~ triangular surface 7 of the body 2. As the opening closure element 3 is ~~drawn~~ powerfully withdrawn, preferably by one and the same person, the shoulder 13 and the shoulder ~~hooking~~ -receiving recess 14 are finally deformed elastically and the closure element 3 is thus released from the box-like body 2. The packaging unit can be re-sealed, ~~since~~ because the shoulder 13 and the recess 14 remain intact after removal of the

closure element 3, therewith thereby enabling the packaging unit to be re-closed by virtue of the shoulder 13 snapping into the shoulder-receiving recess 14.

In another embodiment of the invention, the ~~fastener~~ fastening means 10 is screw-threaded, ~~wherewith~~ wherein the tubular part 4 ~~comprises~~ includes an external screw thread. The cavity 6 of the closure element 3 ~~comprises~~ includes internal threads. The closure element 3 is released from the box-like body 2, by turning the closure element 3 in a given direction so that the element 3 will loosen from the box-like body 2.

In a further embodiment the pipe 5 is placed in the tubular part 4 in which a snap-lock is provided ~~[[;]]~~ (see ~~figures 2A-~~ Figure 2D). The snap-lock is ~~comprised in~~ in the form of an outer toothed ring 12, which preferably encircles the ~~pipe tube~~ 5, and a recess or notch 15 in the cavity 6 of the closure element 3, ~~said~~ The recess 15 also preferably encircling encircles the cavity 6, ~~wherein~~ so that the toothed ring 12 and the recess 15 hook together ~~due to~~ because of the resilient deformation of the ring 12 and the recess 15. Because the ring 12 and the recess 15 remain intact and are not permanently deformed, the packaging unit can be re-closed by virtue of the recess 15 snapping onto the toothed ring 12. The ring 12 and the recess 15 are used so that the pipe 5 is able to expand.

The tubular part 4 is preferably ~~expanded~~ enlarged at a distance outward from the ~~three-sided~~ triangular surface 7, so that the person concerned will be able to encircle the tubular part 4 with his/her lips and therewith drink from the packaging unit 1. ~~This~~ That arrangement avoids lip contact with surfaces of the box-like body 2 that have not been protected by the closure element 3.

The opening closure element 3 ~~shall be~~ is capable of sealing abutment with the ~~three-sided~~ triangular surface 7 of the ~~tubular part 4~~ box-like body 2 in the case of all embodiments, and ~~then~~ preferably also with the outer end of the tubular part 4. ~~This~~ That arrangement also protects the ~~three-sided~~ triangular surface 7 and the tubular part 4 from contamination.

Plastic bridges 18 are preferably fastened between the box-like body 2 and the closure element 3 that abuts said body 2, irrespective of the embodiment concerned. When removing the closure element 3 from the box-like body 2 and ~~therewith~~ thereby opening the packaging unit 1, ~~these~~ the plastic bridges 18 are ~~broken off, therewith severed, thereby~~ indicating that the packaging unit has been opened.

Although a number of embodiments have been described above, it will be understood that the outwardly projecting tubular part 4 of the box-like body 2, the ~~pipe~~ tube 5, and the cavity 6 of the closure element 3 ~~may~~ can be designed in some other appropriate manner without departing from the basic concept of the invention.

The present invention shall ~~not~~ therefore not be considered to be limited to the described and illustrated exemplifying embodiments thereof, since variations can be made within the scope of the accompanying claims.

**CLAIMS**

What is claimed is:

## ABSTRACT OF THE DISCLOSURE

A beverage packaging unit that includes an opening from which the liquid contents of the unit can be dispensed and a closure. The packaging unit is parallelepipedal in shape, including a hollow, box-like body and the closure. The box-like body has a bevelled corner with a triangular surface from which a tubular part that includes the opening extends. The closure includes a generally pyramidal body which is shaped so that when in abutment with the bevelled corner of the box-like body it forms with the box-like body a parallelepipedal packaging unit. The closure includes a cavity for receiving the tubular part. The packaging unit includes co-acting fasteners on the tubular part and also in the cavity for removably retaining the closure on the tubular part.

Figure 1A




Figure 1B




Figure 2A





Figure 2B



~~SUBSTITUTE SHEET (RULE 26)~~

Figure 2C




Figure 2D - Enlargement of the closure unit from figure 2C

